

## Gold King Mine Flow

### Flow from Gladstone Area Mines

The annual discharge of water from the Gold King Mine and 3 nearby mines (Mogul, Red and Bonita, and American Tunnel) was estimated using ESAT data from 2009 through 2014 (Table 1). The average annual runoff flow and the average annual non-runoff flows were weighted to estimate overall annual flow. The four mines discharge approximately 330 million gallons of water per year (based on 2009-2014 flow data). Additional mines in the area also release acid mine drainage. The recent release of 3 million gallons is less than 1 percent of the annual discharge from the four mines.

**TABLE 1**  
**Historic Annual Flows from 4 Mines (Mogul, Red and Bonita, Gold King and American Tunnel)**  
**2009-2012**

	4 Mines Flow			CC06 Flow			
	Flow (cfs)	Days	Annual Flow (gpy)	Flow (cfs)	Days	Annual Flow (gpy)	% of Total
Average of Yearly Average Flow*							
Non-Runoff	1.364	273	240,700,000	0.270	273	47,600,000	20%
Runoff	1.474	92	87,700,000	0.391	92	23,300,000	27%
Total			328,400,000	Total		70,900,000	22%
2009							
Non-Runoff	1.477	273	260,500,000	0.426	273	75,100,000	29%
Runoff	1.623	92	96,500,000	0.452	92	26,900,000	28%
Total			357,000,000	Total		102,000,000	29%
2010							
Non-Runoff	1.227	273	216,400,000	0.418	273	73,800,000	34%
Runoff	1.381	92	82,100,000	0.522	92	31,000,000	38%
Total			298,500,000	Total		104,800,000	35%
2011							
Non-Runoff	1.365	273	240,800,000	0.313	273	55,200,000	23%
Runoff	1.389	92	82,600,000	0.313	92	18,600,000	23%
Total			323,400,000	Total		73,800,000	23%
2012							
Non-Runoff	1.562	273	275,600,000	0.313	273	55,200,000	20%
Runoff	1.389	92	82,600,000	0.313	92	18,600,000	23%
Total			358,200,000	Total		73,800,000	21%

cfs      cubic feet per second

gpy      gallons per year

Calculations based on EPA/ESAT flow monitoring data from 2009-2014. Overall flows for 2013 and 2014 are not shown because spring flows are not available for either year due to snowpack conditions. The average annual runoff flows from 2009-2012 and the average non-runoff flows from 2009-2014 were averaged to calculate the overall average runoff flow. Runoff averages included measurements made during May, June, July. Non-runoff averages included measurements made during other months of the year.

## **Variability of Gold King Mine Flow**

Gold King Mine flow data is available from 2009 through 2014, with multiple sampling events from 2009-2011 and fall sampling from 2012-2014. Gold King Mine spring flow was not measured from 2012 to the present due to high snow and potential avalanche conditions, and flow was not measured during fall 2013 due to the government shutdown. Flow was also measured by START during 2014 and 2015 site visits.

For years with multiple flow measurements (2009, 2010, 2011), the Gold King Mine discharge varied by up to 45 percent within 1 year (2009), when the November flow was 45 percent greater than the August flow.

The Gold King Mine discharge annual average runoff flow varied from the annual average non-runoff flow by up to 22 percent (2010).

Older historic data from START showed flow was 42 gpm in July 2005, 135 gpm in September 2005, and 314 gpm in October 2006. This widely variable flow may have been due to backup of water behind the American Tunnel reaching the elevation of the Gold King rather than an indication of the variability of flow from the Gold King Mine.

Measurements in 2015 included 31 gallons per minute (gpm) on June 24 (similar to Fall 2014), and 69 gpm on both July 15 and July 23.

